

Optical Network Media Conversion



ETHERNET AND FAST ETHERNET STANDALONE MEDIA CONVERTERS									ETHERNET AND FAST ETHERNET STANDALONE MEDIA CONVERTERS								
SUBCAT	FEATURE	AFMC13	AFMC101XL	AFMC102XL	AFMC103XL	AFMC103LH	AFMC104XL	AFMC115XL	AFMC116XL	AFFS201	AFFS202	ATPC232/POE	AFFS232	AFFS232/1	AFFS232/2	AFFS238A/1	AFFS238B/1
PORTY	Port 1	10T	100TX	100TX	100TX	100TX	100FX MMF (SC)	10T or 100TX	10T or 100TX	10/100TX	10/100TX	10/100TX	10/100TX	10/100TX	10/100TX	10/100TX	10/100TX
	Port 2	10FL (ST)	100FX (ST)	100FX (SC)	100FX (SC)	100FX (SC)	100FX (SC)	10FL (ST) or 100FX (ST)	10FL (SC) or 100FX (SC)	100FX (ST)	100FX (SC)	100FX (SC)	100FX (SC)	100FX (SC)	100FX (SC)	100FX (SC)	100FX (SC)
	Typ światłowododu	MMF	MMF	MMF	SMF	SMF	SMF	MMF	MMF	MMF	MMF	MMF	MMF	SMF	SMF	BIDI - SMF	BIDI - SMF
IEEE STANDARD		10FL	100FX	100FX	100FX	100FX	100FX	100SX	100SX	100FX	100FX	100FX	100FX	100FX	100FX	100FX	100FX
Tx DŁUGOŚĆ FALI		850nm	1310nm	1310nm	1310nm	1310nm	1310nm	850nm	850nm	1310nm	1310nm	1310nm	1310nm	1310nm	1310nm	1310nm	1550nm
Rx DŁUGOŚĆ FALI		850nm	1310nm	1310nm	1310nm	1310nm	1310nm	850nm	850nm	1310nm	1310nm	1310nm	1310nm	1310nm	1310nm	1310nm	1310nm
MAKSYMALNA DŁUGOŚĆ ŚWIATŁOWODU		2km	2km	2km	15km	40km	15km	2km	2km	2km	2km	2km	2km	15km	40km	15km	15km
FUNKCJONALNOŚĆ	Rate and speed																
	MissingLink support																
	Smart MissingLink support																
	Maksymalny rozmiar ramki	9KB	9KB	9KB	9KB	9KB	9KB	9KB	9KB	1532bytes	1532bytes	1916bytes	1532bytes	1532bytes	1532bytes	1532bytes	1532bytes
Diody Sygnalizacyjne		6	7	7	7	7	7	8	8	7	7	13	9	9	9	9	9



GIGABIT STANDALONE MEDIA CONVERTERS						
SUBCAT	FEATURE	AFMC1004	AFMC1008/GB	AFMC1008/SP	AFGS2002/SP	ATPC2002POE
PORTY	Port 1	1000T	1000T	1000T	10/100/1000T	10/100/1000T
	Port 2	1000SX	GBIC	SFP	SFP	SFP 100 or 1000Mbps
	Typy światłowododu	SC	SC *	LC *	LC *	LC *
IEEE STANDARD		1000SX	1000SX and LX	1000SX and LX	1000SX and LX	100FX and 1000X
Tx DŁUGOŚĆ FALI		850nm	Depends on GBIC	Depends on SFP	Depends on SFP	Depends on SFP
Rx DŁUGOŚĆ FALI		850nm	Depends on GBIC	Depends on SFP	Depends on SFP	Depends on SFP
MAKSYMALNA DŁUGOŚĆ ŚWIATŁOWODU		550m	Depends on GBIC	Depends on SFP	Depends on SFP	Depends on SFP
FUNKCJONALNOŚĆ	Rate and speed					
	MissingLink support					
	Smart MissingLink support					
	Maksymalny rozmiar ramki	9KB	9KB	9KB	1536bytes	1536bytes
	Diody sygnalizacyjne	8	8	8	11	15