

Power consumption table of **CyberPower's** Line-Interactive and Offline UPS Models:

Model	Power Consumption
EX650E	4.0W
EX850E	5.0W
DX600E	4.0W
DX800E	4.1W
Value 600ELCD- GP /Non GP	2.6 W / 10.2W
Value 800ELCD- GP /Non GP	2.6 W / 10.2W
Value 1000ELCD- GP /Non GP	3.2 W / 11.4W
Value 1200EILCD-GP	6.0W
Value 1500EILCD-GP	6.0W
Value 2200EILCD-GP	7.5W
BR650ELCD	2.9W
BR850ELCD	3.0W
OR600ELCDRM1U	4.0W
OR1000ELCDRM1U	4.9W
OR1500ELCDRM1U	5.3W
CP1050EAVRLCD	4.1W
CP1350EAVRLCD	5.0W
CP1500EAVRLCD	5.0W
CP900EPFCLCD	3.9W
CP1300EPFCLCD	4.9W
CP1500EPFCLCD	4.9W
PR750ELCD	5.2W
PR750ELCDRT1U	8.1W
PR1000ELCDRT1U	8.8W
PR1000ELCDRT2U	9.0W
PR1500ELCDRT2U	9.0W
PR2200ELCDRT2U	9.0W
PR3000ELCDRT2U	9.1W
PR1000ELCDRTXL2U	9.0W
PR1500ELCDRTXL2U	9.0W
PR2200ELCDRTXL2U	9.0W
PR3000ELCDRTXL2U	9.2W
PR5000ELCDRTXL5U	11.2W
PR6000ELCDRTXL5U	11.5W