

C91

PROFILE

Centerm C91 is a specially designed thin client based on high performance quad-core CPU. It offers desktop-grade Android operating system and delivers rich multimedia and PC-like user experience.

FEATURES

- **Professional android platform thin client**
With the specially designed android operating system, C91 offers rich android applications and optionally supports app download from Google Play.
- **Low TCO Solution**
Low price, low power consumption and high performance guarantee it a low TCO solution.
- **High Performance**
Full-HD 1080p video playback supported and offers a powerful platform for rich multimedia applications.
- **Compact, Flexible & Secure**
Small size, fan-less design, VESA mountable, anti-theft keyhole.
- **Environment friendly**
Low CO2 emission, low heat emission, noise-free and space saving.





CB



Connectivity

1. Power Button
2. USB 2.0 Port
3. USB 2.0 Port
4. Reset Button
5. Power Jack



1. VGA Port
2. HDMI Port
3. 10/100 Ethernet RJ45
4. Kensington Lock
5. MicroSD Port
6. Audio Output
7. Audio Mic In

SPECIFICATION

SYSTEM	
Processor	ARM Quad-Core 1.6GHz
Available Operating System	Based on Android 4.2.2
VDI/HSD Support	Microsoft RDP 8.1
Management	CCCM
MEMORY	
RAM (DDR3)	1GB (Max up to 2GB)
Storage (Flash)	8GB EMMC (Onboard)
DISPLAY	
Port	VGA x 1 , HDMI x 1
Resolution	Up to 1920x1080 @ 60Hz (Not support 1680x1050 for VG)
Color Depth	Up to 32bits true color
Dual Display	Supported
Network	
LAN	x1 (10/100 Mbps Base-T Fast Ethernet, RJ-45)
WLAN	- Optional integrated 802.11 b/g/n wireless module
I/O PERIPHERAL INTERFACE	
USB 2.0	x2 (front), x2 (side)
RJ-45	x 1
Micro-SD Port	x1 (Max up to 32 GB)
AUDIO	
Ports	Front: Line-out x 1 , Mic-in x 1 , (1/8-inch mini jack)
DIMENSION	
Device	93.5mm x 93.5mm x 20.4mm
Packaging	157.5mm x 144.5mm x 86mm
Net Weight	0.21 kg
Power	
Adapter	Worldwide auto-sensing 100-240V AC, 50/60 Hz, 5V/3A DC
Power Consumption	Max 5.28w
Mounting	
VESA Bracket	VESA Mounting Kit
Kensington Lock	Built-in Kensington Lock Slot
ENVIRONMENT	
Cooling	Fan-less Convection
Operation Temperature	0°C to 40°C
Relative Humidity	30% to 90% non-condensing

Centerm Information Co. , Ltd (China)

Add: 2F, #22 Star-net Scient Plaza, Juyuanzhou, #618 Jinshan Road,
Fuzhou, Fujian, China 350002
Tel: +86-591-28053888 ext 8757

Centerm Information APAC (Singapore)

Add: 18 Kaki Bukit Road 3, Entrepreneur Business Centre, # 04-12,
Singapore 415978
Tel: +65 9015 1946