



Specifications of OSE-201 IP Camera

Firmware

Video Compression	MPEG4 Simple Profile
Operating Software	uCLinux
User Name & Password Access	2-level user's account access
IE Browser	6.0 and above
Image Quality Adjustment	Brightness, Saturation, Contrast, Hue, and Quality
Frame Adjustment	1 - 30 fps adjustment
Pan-tilt-zoom adjustment	Pelco D/P protocols, Lilin PIH7000, DynaColor, AcutVista,
Setup	User can setup functions such as image quality, bandwidth, fps, audio, motion detection, pan-tilt-zoom, timer adjustment, DI/DO, user account, camera log file, email, default value, snapshot email with alphabetical strings, location of camera, host name
Timer Display	Yes (initial timer setup and synchronizing with PC setup)
Multi Motion Detection Zones Setup	Embedded
DI/DO	Triggered condition (high or low volt triggered), activate or disable
Network	General IP address setup, SMTP, HTTP, and streaming setup
Event Triggered Info Setup	Trigger condition and action,
DDNS	Support
DHCP	Support
Log File Inquiry	Support
Decode	OCX
Image Format	NTSC/PAL
Image Resolution	NTSC: 352*240 ; PAL: 352*288
Frame (frame per second)	NTSC: 30 / PAL: 25