



SS-8801E/R

The Redundant RAID system setup an important milestone for MaxTronic approaching to critical high-end enterprise demands. With active-active redundant controller architecture for full failover, the latest 4Gb FC-SAS host interface with advanced high performance CPU supports higher data operation rate. Powerful hardware engine, high scalable expansion options and user-friendly management interface make it the best choice for fault tolerance, high performance solutions.

Ideal Application

- Enterprise Storage
- Online SAN Solution
- Video Editing
- Clustering/HA Solution
- Virtualization Cloud Storage

FEATURES AND BENEFITS

Single Controller Upgradable

Single controller model is field upgradable to a redundant solution. You could upgrade single to redundant by directly insert another controller module, So you can just configure a Active/Active solution by use both controller simultaneously for double I/O throughput, or if you prefer to have Active/Standby solution, you can put one controller on "standby", so it becomes a backup for the other one.

Innovate New Array Structure

The system features a new innovate array structure that hierarchically organizes storage objects. With this structure, physical drives are combined into Disk Groups (DG). DGs are subdivided into Logical Disks (LDs) where arrays are created. LDs can be combined together to form a striped Volumes. Either Volumes or LDs can be pointed to a LUN which are then presented to the host computer.

JBOD Expansion

This feature provides users the option to attach external SAS JBOD unit to expand the capacity of their storage solution. By cascading the RAID-less SAS JBOD unit helps reduce the total cost of ownership.

Flexible Compatibility

Advanced 4Gb FC host interface supports the former 2Gb FC and 1Gb FC interface with no hardware modification request. The SAS disk interface supports the most cost effective drive to lower TCO.

Centralized management by RAIDGuard Central

RAIDGuard Central (RGC), a free centralized management utility provides centralized monitoring multiple RAID systems by through Ethernet at a local area network. Easier install RGC to a normal PC as an agent and then any PC/server could monitor to RAID system remotely. Allow customer to warning the engineer real-time with mail sending and most popular web messenger: MSN.

Fibre



Technical Specifications

Host Channel

Model No.	SS-8801E / SS-8801R
Data Transfer Rate	Up to 4Gbps per port
External Connector Type	SFP(*1)

*1. SFP transceiver is not included.

*2. Support up to 120 disks (include local chassis)

Host Interface	4Gb FC
Host Channel No.	2 / 4
JBOD Expansion	Yes (*2)

Hardware

Controller No.	Single (Upgradable) / Dual (Redundant)
Controller CPU	Intel IOP34x
Disk Channel No.	24
Hot Swap Power Supply	350W, Redundant 2+1
Battery Backup	Optional / Yes

*3. Support SATA drive needs AA-MUX tray board equipped.

Cache Memory	2048-4096 MB DDR II
Disk Interface	SAS (SATA compatibility)(*3)
Hot Swap Disk Tray	24 x 3.5" swappable trays
AC Input Voltage	100 to 240V (+/-10%), 47 to 63 Hz
Hot Swap Fan Module	4

RAID Functions

RAID Levels	JBOD, 0, 1, 3, 5, 6, 10, 30, 50, 60, NRAID
RAID Features	<ul style="list-style-type: none">- Support multiple RAID levels and stripe size- Support local hot spare and global hot spare- Online background initialization- Online RAID level and stripe size migration- Online capacity expansion and shrink- Online disk group de-fragmentation for free space consolidation- Online drive traveling and array roaming- Online array recovery
Advanced Data Reliability Assurance	SMARTCor. Function (DST, DS, DC)

RAID Management

Front Panel LCD and Buttons	Easy access for configuration and status report	Management AP	Java-based management GUI for configuration and status monitoring
RS-232 Terminal	Command Line Interface (CLI) for configuration and status report	Event Notification	Built-in buzzer, e-mail, SNMP trap (*3), downloadable event records (up to 1024)
GUI	Embedded Ethernet connection, web browser-based RAID management GUI for configuration and status monitoring		

Environment Specification

Humidity	20% to 80% non-condensing	Safety Regulatory	UL, CUL, CB
Operating Temp.	5°C to 40°C (41°F to 104°F)	EMC Standard	FCC, CE, C-Tick, BSMI
Non-operating Temp.	-25°C to 60°C (-13°F to 140°F)		

Dimension and Weight

Physical Dimension	485(W) x 565(D) x 176(H) mm	Physical Weight	34Kgs (without drives)
Packed Dimension	635(W) x 805(D) x 565(H) mm	Packed Weight	44Kgs (without drives)

* Specifications and product offerings may vary without notice.

* Various trademarks belong to their respective owners.

Headquarters
MaxTronic International Co., Ltd.
TEL : 886-2-2218 4875
FAX : 886-2-2218 4896
<http://www.maxtronic.com.tw>

America
Arena-MaxTronic Inc.
TEL : 1-626-334 1888
FAX : 1-626-334 6888
<http://www.maxtronic.com>

China
欧骅股份有限公司 北京办事处
TEL : 86-10-5873 4580~83
FAX : 86-10-5873 4585
<http://www.maxtronic.com.cn>