



# USB/Firewire RAID Subsystem



SA-3184S

## User Friendly, Lowest Total Cost, Easy Management

Arena compact 4bays RAID unit an entry level, user friendly and cost effective solutions designed for small business and SOHO users. With an on-board ASIC, USB/Firewire host connectivity, deliver unsurpassed performance with RAID levels 0, 0+1, 5, and 5+spare. Setup is quick and easy using dip switches accessible from the rear panel. Connecting to the host is plug-and-play, transparent to various operating systems.

### FEATURES HIGHLIGHT

#### Extreme Performance

The SA-3184S features high-speed Firewire 800 and USB 2.0 combo host interface with 4 SATA disk drives which support up to 2TB capacity combined with hardware XOR RAID technology.

#### Easiest / Quickest Installation

Requires No driver to install, plug and play installation.

#### User-friendly Management

Front Panel LCD and Buttons, Terminal and In-band GUI, make RAID functions set up and managed in an easier way.

#### RAID Function

- Easy configuration and access through button and/or dip switch
- Connection through USB or Firewire connector, without add-on HBA
- RAID Level: 0, 0+1, 5, 5+Spare
- Global Hot spare
- Event Notification

# USB/Firewire

# Janus II Series Desktop 4bay USB/Firewire RAID Subsystem



## SPECIFICATION

### Hardware Components

Model No.	SA-3184S
RAID Controller	Single
No. of Host Channels per Controller	Firewire/USB2.0
Cache Memory Per Controller	2MB Buffer
No. of Drives	4
Hot Swap Power Supply	1 x 200W
Hot Swap Fan Module	1
Dimension	Desktop 153(W) x 287(D) x 206(H) mm
Weight (without drives)	6 Kgs

### Feature Highlights

RAID Volume	RAID Level 0, 0+1, 5, 5+spare Global and dedicated hot spare Online volume expansion Auto volume rebuilding
Configuration	Front Panel LCD and Button
Notification	Built-in buzzer
OS Support	Windows; Linux; Mac

### Requirements

AC Input	100 to 264V(+/-10%), 47 to 63 Hz
Operating Temperature	5°C to 40°C
Humidity	20% to 80% non-condensing

- \* Specifications and product offerings may vary without notice.
- \* Various trademarks belong to their respective owners.

#### Headquarters

MaxTronic International Co., Ltd.  
TEL : 886-2-2218 4875  
FAX : 886-2-2218 4896  
<http://www.maxtronic.com>

#### America

Arena-MaxTronic Inc.  
TEL : 1-626-962 1888  
FAX : 1-626-337 88 22  
<http://www.maxtronic.com>

#### China

欧骅股份有限公司 上海办事处  
TEL : 86-021-62708599  
FAX : 86-021-62708580  
<http://www.maxtronic.com>